According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 1111

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone num- : +49 8142 3051 517

ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

ways.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

Chemical nature : Active agent with propellant and solvent.

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concen- tration limit M-Factor Notes	Concentration (% w/w)			
propane	74-98-6 200-827-9 601-003-00-5	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 20 - < 30			
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	920-750-0	Flam. Liq.2; H225 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 10 - < 20			
isobutane	75-28-5 200-857-2 601-004-00-0	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10			
Substances with a workplace exposure limit :							
butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 50 - < 70			

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water.



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire- : Fire Hazard

a brand of

FREUDENBERG

According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

fighting Do not let product enter drains.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod- :

ucts

Carbon oxides Metal oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

EWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular na-

tional regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis			
butane	106-97-8	STEL	750 ppm	GB EH40			
			1,810 mg/m3	(2007-08-01)			
	Further inforn	Further information: Capable of causing cancer and/or heritable genetic dam-					
	age.	age.					
		TWA	600 ppm	GB EH40			
			1,450 mg/m3	(2007-08-01)			
	Further inforn	Further information: Capable of causing cancer and/or heritable genetic dam-					
	age.	age.					

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

Version **Revision Date:** Date of last issue: 20.06.2018 Print Date: Date of first issue: 30.03.2013 2.2 07.12.2021 07.12.2021

> Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the spe-

cific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance aerosol

Colour colourless

Odour hydrocarbon-like

Odour Threshold No data available

рΗ Not applicable

substance/mixture is non-soluble (in water)

Melting point/range No data available

Initial boiling point and boiling : < -20 °C (1,013 hPa)

range

-20 °C Flash point

Method: Abel-Pensky

Evaporation rate No data available

Flammability (solid, gas) Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

15 %(V)

Lower explosion limit / Lower :

flammability limit

0.6 %(V)

Vapour pressure 4,920 hPa (20 °C)

Relative vapour density No data available

Relative density 0.6 (20 °C)

> Reference substance: Water The value is calculated



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

Density : 0.60 g/cm3

(20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : > 200 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

>150 °C small quantities of formaldehyde may be formed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fa-

tigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Remarks: This information is not available.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

: Remarks: No data available

STOT - single exposure

Product:

Exposure routes : Inhalation

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

Date of last issue: 20.06.2018 Version Revision Date: Print Date: 07.12.2021 Date of first issue: 30.03.2013 07.12.2021 2.2

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Repeated dose toxicity

Product:

: This information is not available. Remarks

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks Information given is based on data on the components and

the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish Remarks: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

Date of last issue: 20.06.2018 Version Revision Date: Print Date: Date of first issue: 30.03.2013 2.2 07.12.2021 07.12.2021

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product:

Biodegradability Remarks: No data available

ity

Physico-chemical removabil- : Remarks: No data available

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Biodegradability : Result: Readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

propane:

Partition coefficient: n-

octanol/water

log Pow: 2.36

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Bioaccumulation : Remarks: Not applicable

Partition coefficient: n-

octanol/water

: Remarks: No data available

isobutane:

Partition coefficient: nlog Pow: 2.88

octanol/water Method: OECD Test Guideline 107

butane:



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

Partition coefficient: n- : log Pow: 2.89

octanol/water Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Endocrine disrupting poten-

tial

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological infor-

mation

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company.

According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number

ADR : UN 1950

RID : UN 1950

IMDG : UN 1950

IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

Version Date of last issue: 20.06.2018 Print Date: Revision Date: 2.2 07.12.2021 Date of first issue: 30.03.2013 07.12.2021

Packing group Not assigned by regulation

Labels 2.1 **EmS Code** F-D, S-U

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

203

Labels Flammable Gas

IATA (Passenger)

Packing instruction (passen-203

ger aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Labels Flammable Gas

14.5 Environmental hazards

Environmentally hazardous no

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57).

REACH - List of substances subject to authorisation : Not applicable

> a brand of FREUDENBERG

According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

: P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous sub-

stances.

P3a FLAMMABLE AEROSOLS

18 Liquefied extremely flammable

gases (including LPG) and natu-

ral gas

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 90.01 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of R-Phrases

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-

stance is a specific isomer or a mixture of isomers.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The

According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Full text of H-Statements

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-

stance is a specific isomer or a mixture of isomers.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in



According to REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 - GB



OKS 1111

VersionRevision Date:Date of last issue: 20.06.2018Print Date:2.207.12.2021Date of first issue: 30.03.201307.12.2021

China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TSCA -Toxic Substances Control Act (United States): UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture:

Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment STOT SE 3 H336 Based on product data or assessment Asp. Tox. 1 H304 Based on product data or assessment Aquatic Chronic 3 H412 Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.